



YANMAR L70V

**4.8kW (6.4hp) @
3600r/min⁻¹**

Type	4-stroke, vertical cylinder, air-cooled diesel engine
No. of Cylinders	1
Bore x Stroke (mm)	78 x 67
Displacement (litres)	0.320
Continuous Rated Output	
r/min ⁻¹	3600
HP SAE	5.8
kW	4.3
PS	5.9
Max Rated Output	
r/min ⁻¹	3600
HP SAE	6.4
kW	4.8
PS	6.5
High Idling r/min ⁻¹	3800
Dry Engine Weight	
with Electric Start (lbs/kg)	90.4 / 41
Dry Engine Weight	
without Electric Start (lbs/kg)	79.4 / 36
Cooling System	Forced Air by Flywheel Fan
Lubrication System	Forced lubrication with Trochoid Pump
Starting System	Electric Start / Recoil Start
Dimensions (inches/mm)	
Length x Width x Height	14.9 / 378 x 16.6 / 422 x 17.8 / 453
Engine Oil Pan Capacity	
Dipstick Upper Limit	1.11 qt / 1.05 litres
Dipstick Lower Limit	0.69 qt / 0.65 litres
Fuel Tank Capacity (recommended)	2.85 qt / 2.7 litres

